

SWING BARRIER GATE

Zenidea Swing Barrier Gate is an optical turnstile equipped with bi-directional swing barriers to accommodate high traffic flows and detect tailgating. Built with infrared sensors and intelligent motors, pedestrian movement is accurately monitored which allows smooth in-and-out traffic. The barrier opens after access authorization and closes quickly behind the authorized user. The system will automatically set on an alarm to deter people without authorization or efforts to push against the barrier. Zenidea Swing Gate is an ideal solution to meet the demand of customers for high-end safety technology.



ZENIDEA SWING BARRIER GATE

FEATURES PATENTED TECHNOLOGY



600
800
mm

PASSAGE
WIDTH



25
40
pers/min

SINGLE ACCESS
FLOW RATE



60
pers/min

FREE ACCESS
FLOW RATE



0.5
0.8
sec

OPENING / CLOSING



IP 41-54*

PROTECTIVE LEVEL



ANTI-TAILGATING



BI-DIRECTIONAL



ACCESS CONTROL
SYSTEM



MANUAL
CONTROL

KEY FEATURES:

- The unit can be featured to fail safe in case of emergency such as power outage and fire. The barriers will be opened to allow fast evacuation. Qualified by EN13617:2015.
- The system will sound an alarm if someone enters without authorization, or from the wrong direction.
- Monitored by infrared sensors, the movement control system can detect tailgaters.
- In normal operating mode, the barrier closes after pedestrian passage. If no passage is detected after 3 seconds, access authorization will be canceled and the barrier will be closed.
- The patented mechanism means quick reaction from signals and years of worry-free operation.

Technical Specifications

Housing Dimensions	1200*140*100mm
Body Material	SUS304, Acrylic, Tempered Glass
Width of Passage	600mm(Customizable Max 800mm)
Housing Thickness	0.8mm+1.0mm
Motor	DC24V Brushless Electric Motor
Passage Direction	Bi-directional
Flow Rate	25-40 People Per Minute
Protection Level	IP53
Life Cycle	6 Million Times
Operation Mode	Biometrics, IDIC, Remote
Infrared sensor	4 Pairs
Power	40 ~ 60W
Power Supply	220V±10% 50Hz
Operating Temperature	-15℃ ~ 70℃
Operating Humidity	20%~95% No Condensation
Communication	Dry Contact, RS232/RS485
Operating Environment	Indoor

