Flap Barrier

Zenidea Flap Barrier is built in a unique style. Installed with two flap-shaped barriers that can be fully retracted into the cabinet to allow authorized personnel. The inbuild infrared sensors monitor pedestrian movement with pinpoint accuracy. Flap barrier opens only after access approval, then the barrier quickly closes to deter tailgaters, and it will automatically sound an alarm if someone enters without authorization. Zenidea Flap Barrier is the ideal product to choose if you are looking for a stylish and secure entry solution.

ZENIDEA FLAP BARRIER GATE

FEATURES PATENTED TECHNOLOGY

KEY FETURES:

- The unit is triggered in a fail-safe mode in case of emergency such as power outage and fire. The barriers will be opened to allow fast evacuation.
- The system will sound an alarm if someone enters without authorization, or from the wrong direction.
- Monitored by infrared sensors, the movement control system can detect tailgaters as close as 5cm apart.
- In normal operating mode, the barrier closes after pedestrian passage. If no passage is detected after 3 seconds, access authorization will be canceled and the barrier will be closed.
- The patented mechanism means quick reaction from signals and years of worry-free operation.

Technical Specifications

Pedestal Dimension	1505*300*980mm
Housing Material	Acrylic, Tempered Glass, Aluminium Alloy
Width of Passage	550mm
Housing Thickness	10.0mm+3.0mm
Motor	24V DC Brushless Motor
Protection Level	IP51
Traffic Direction	Bi-Directional
Flow Rate	30-45/min
Operating Temperature	-15～70℃
Operating Humidity	20%~95% No Condensation
Access Method	Biometrics, RFID, QR, Romote
Life Cycle	9 Million Times
Infrared Sensor	5 Pairs
Power Consumption	40-60W
Power Supply	220V±10% 50Hz
Operating Evironment	Indoor
Communication	Dry Contact, RS232, RS485


155
1505
1505
155
1150
1150
980
300